



**Eigenschaften:**

- 24 Positionsspeicherplätze
- IR Fernbedienung
- 2 Digit LED Display
- Für Antennen bis zu 3m

**Technische Daten:**

	HH100	HH120
Maximum Antenna Diameter	100 cm	120 cm
Maximum Antenna Weight	12 kg	17 kg
Pole Support Diameter	from 50 to 83 mm	from 50 to 83 mm
Antenna Support Length	125 mm	180 mm
Antenna Support Diameter	54 mm	54 mm
<b>Operational Data</b>		
Operating Protocol	DiSEqC 1.2	DiSEqC 1.2
Rotation Angle	+/- 62°	+/- 62°
Rotation Speed	1,8°/s @ 18 V 1,2°/s @ 13 V	1,1°/s @ 18 V 0,8°/s @ 13 V
Programmable Positions	49 Satellites	49 Satellites
Preset Positions	28 Satellites	28 Satellites
Mechanical Limits	+/- 70°	+/- 70°
Software Programmable Limits	from 5° to 62°	from 5° to 62°
Fine Tuning	impulse 0.1	impulse 0.1
Inclination on the Pole	from 15° to 70°	from 15° to 70°
Connectors	F - Type	F - Type
Connections	Sat Coaxial Cable	Sat Coaxial Cable
<b>Power Requirements</b>		
Operating Power Supply	13 / 18 Vdc	13 / 18 Vdc
Consumption in Stand-by Mode	30 mA	30 mA
Consumption in Operating Mode	190 mA	190 mA
Starting Consumption	350 mA (max.)	350 mA (max.)
<b>General</b>		
Operating Temperature Range	-40°C ~ + 80°C	-40°C ~ + 80°C
Maximum relative Humidity	100 %	100 %
Weight	3 kg	3,2 kg