

TF 7710 HSCI

High Definition Digital Satellite Receiver with Common Interface.



Features:

- Fully DVB-S/DVB-S2 (H.264) HD compliant
- 2 Common Interfaces for Conax, Cryptoworks, Irdeto, Seca, Viaccess, Etc
- Multilingual menu, audio and subtitle
- Teletext
- 5000 services list
- 30 favourite service lists
- S/PDIF for Dolby Digital audio output
- Component video output (Y/Pb/Pr)
- USB port for firmware update

Specifications:

Frequency Range	950 - 2150 MHz
Demodulation	QPSK
Aspect Ratio	4:3, 16:9
Video Resolution	576i, 576p, 720p, 1080i
HDMI	HD Video/Audio Output
TV SCART	Video CVBS/S-VIDEO/RGB/YPbPr output, Audio L/R output
VCR SCART	Video CVBS output, Audio L/R output (Input for bypass) S-Video Video S-VIDEO output
Component	YPbPr output
RCA A/V	Video CVBS output, Audio L/R output
RS-232C	max. 115.2Kbps
USB	2.0 Host
Power Supply	90 - 250VAC, 50/60Hz
Power Consumption:	
Running	Max. 23W,
Standby	7W
Size (WxHxD)	340 x 60 x 265 mm
Weight (Net)	2.44 kg