

## Maximum A/V Link System III



Wireless transmission of audio and video signal

- Antenna embedded
- Remote control the A/V source with IR Extender
- Low power consumption
- NTSC/PAL video format available
- Compact size with streamlined shape design
- 4 selectable channels and Auto scan (Dip switch)
- Range up to 300 feet

### Frequency range

Transmitter: 2400 MHz ~ 2483 MHz

Receiver: 2400 MHz ~ 2483 MHz

### Sender power

10 dBm (Typ.)

### Channel number

Transmitter: 4 (2414, 2432, 2450, 2468 MHz)

Receiver: 4 (2414, 2432, 2450, 2468 MHz)

### Frequency stability:

+/- 100 KHz

### L.O. Stability:

+/- 100 KHz

### Video level

Input: 1 Vp-p (Typ.)

Output: 1 Vp-p (Typ.)

### Audio level

Input: 1 Vp-p (Typ.)

Output: 1 Vp-p (Typ.)

### Sensitivity

Receiver: -85 dBm

### Supply voltage

Transmitter: 9V (Typ.)

Receiver: 9V

### Power consumption

Transmitter: 90 mA (Typ.)

Receiver: 200 mA (Typ.)

### Antenna

Transmitter: Dipole

Receiver: Dipole

### Operating temperature

Transmitter: -10°C - +60°C

Receiver: -10°C - +60°C

### Dimensions (W x H x D):

Transmitter: 41 x 115 x 102 mm

Receiver: 41 x 115 x 102 mm